

Canadyne AirBoom MP Model 12/18, 22 PVC

Part Number: 10286

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height	30.0 in	762 mm
Diameter	12 in	305 mm
Draft	18.0 in	457 mm
Standard Length	82 ft	25 m
Fabric Weight	22 oz/yd ²	750 g/m ²
Fabric	PVC coated Polyester	
Colour	Orange standard, others available	
Boom Weight, approx.	1.9 lbs./ft	2.8 kg/m
Buoyancy/Weight Ratio	26:1	
Internal Air Chamber Length	16.4 ft	5 m
Separation of Chambers	Internal bulkheads, smooth exterior profile	
Inflation Valve	Monsoon Inflation/Deflation	
Pressure Relief	Leaflet A6 valve in each chamber	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Toggle Pins	3/8" (9.5 mm) stainless steel, spring loaded with lanyard	
Ballast	Grade 30, hot dipped galvanized steel chain	
Ballast Size	5/16 in	8.3 mm
Ballast Weight	0.83 lbs./ft	1.2 kg/m
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m

All above values are nominal and subject to change without notice.

Canadyne AirBoom MP Model 18/24, 22 PVC

Part Number: 10287

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height (Deflated)	52.0 in	1320 mm
Air Chamber Diameter	18 in	457 mm
Draft	24 in	610 mm
Standard Length	82 ft	25 m
Fabric Weight	22 oz/yd ²	750 g/m ²
Fabric	PVC coated Polyester	
Colour	Orange standard, others available	
Internal Air Chamber Length	16.4 ft	5 m
Separation of Chambers	Internal bulkheads, smooth exterior profile	
Inflation Valve	Monsoon Inflation/Deflation in each chamber	
Pressure Relief	Leaffield A6 valve in each chamber	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Toggle Pins	3/8" (10 mm) stainless steel, spring loaded with lanyard	
Boom Weight	2.8 lb/ft	4.2 kg/m
Ballast	Grade 30, hot dipped galvanized steel chain	
Ballast Size	3/8 in	10 mm
Ballast Weight	1.21 lbs./ft	1.8 kg/m
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m

Canadyne AirBoom MP Model 18/24, 23 PU

Part Number: 10288

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height (Deflated)	52.0 in	1320 mm
Air Chamber Diameter	18 in	457 mm
Draft	24 in	610 mm
Standard Length	82 ft	25 m
Fabric Weight	23 oz/yd ²	785 g/m ²
Fabric	PU coated Polyester	
Colour	Orange standard, others available	
Internal Air Chamber Length	16.4 ft	5 m
Separation of Chambers	Internal bulkheads, smooth exterior profile	
Inflation Valve	Monsoon Inflation/Deflation in each chamber	
Pressure Relief	Leaffield A6 valve in each chamber	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Toggle Pins	3/8" (10 mm) stainless steel, spring loaded with lanyard	
Boom Weight	2.9 lb/ft	4.3 kg/m
Ballast	Grade 30, hot dipped galvanized steel chain	
Ballast Size	3/8 in	10 mm
Ballast Weight	1.21 lbs./ft	1.8 kg/m
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m