



## Canadyne Technologies

The Canadyne Multi Skimmer is a versatile, multi-functional selective **3 in 1** oleophilic oil skimmer that achieves an extremely high ratio of recovered oil in relation to water. The standard unit is fitted with a rotating brush unit, while optional drum and disk modules are easily interchanged to enable recovery of a complete range of oils and viscosities from diesels and kerosenes up to heavy crudes.







Skimmer Head	1218/1	1230/1	1230/2	
Recovery Module Standard (Optional)	Brush (Disk and/or Drum)	Brush (Disk and/or Drum)	Brush (Disk and/or Drum)	
Recovery Rate, m3/hr (USGPM)	12 (52)	20 (88)	40 (176)	
Number of Recovery Modules	1	1	2	
Free Water Recovery	Less than 2%	Less than 2%	Less than 2%	
Viscosity Range	Variable, as per pump	Variable, as per pump	Variable, as per pump	
Skimmer Head Length, m (in.)	0.87 m (34")	0.97 m (38")	1.50 m (59")	
Skimmer Head Width, m (in.)	1.02 m (40")	1.32 m (52")	1.22 m (48")	
Skimmer Head Height, m (in.)	0.46 m (18")	0.46 m (18")	0.53 m (21")	
Skimmer Head Weight, kg (m) (with drum	43 kg (94 lbs)	54 kg (118 lbs)	91 kg (200 lbs)	
module(s))				
Construction, Finish	All welded marine grade aluminum and SS, powder coated orange			
Recovery Module Attachment	Spring Loaded Stainless Steel Quick Release			
Oil Flow	No sharp 90 degree transitions, or requirement for cleanout port			
Handles	Four (4), side mounted			
Drive, Power	Hydraulic Motor (onboard), Diesel driven hydraulic (DH)			
Hydraulic Hoses	12.5 mm x 15 m ( $\frac{1}{2}$ " x 50') twin wire c/w caps and plugs, 2 sets (1 for motor, 1 for pump)			
Fittings	Brass quick disconnects			

Brass quick discornices	
ONBOARD (OB)	REMOTE (RE)
Centrifugal, detachable Hydraulic 10 m (33') discharge hose Via Camlock	Diaphragm, Portable Diesel / Hydraulic / Gas 10 m (33') discharge hose, 20 m (66') suction
	ONBOARD (OB)  Centrifugal, detachable Hydraulic 10 m (33') discharge hose

## **PowerPack**

FOWEI FACK				
Motor Type, Model	Diesel Engine, Air Cooled			
Horsepower (HP):	10 HP (7.5 kW)	10 HP (7.5 kW)	15 or 20 HP (12 or 15 kW)	
Start:	Recoil / Electric	Recoil / Electric	Electric standard	
Weight, Dimensions:	145 kg (320 lbs.)	145 kg (320 lbs.)	200 kg (440 lbs.)	
(uncrated)	40" L x 34" W x 36" H	40" L x 34" W x 36" H	60" L x 41" W x 36" H	
Pump:	Hydraulic, Direct Coupled			
Gauges:	Hydraulic Pressure, Oil Level and Temperature			
Hydraulic Tank:	20 L (6 gallon)			
Controls:	Dual (Speed/Direction), for recovery bank and transfer pump			
Frame:	Square aluminum tubing			
Cart:	Heavy duty tires, SS shaft, roller bearing			
Colour, Finish:	Orange, Powder coated finish			







All Canadyne MultiSkimmer systems come complete with user manuals, all hydraulic and transfer hose sets, export crated.