



# PermaBoom HD

## Application Guide

**PermaBoom** is the only choice for permanent installation in and around marine facilities. Extremely rugged construction and excellent resistance to weathering provide years of reliable, low-cost service.

Perfect for oil and debris containment and for exclusion of floating pollutants from sensitive facilities or areas.



Canadyne **PermaBoom HD** (Heavy Duty) is a rugged, solid buoyancy boom used for permanent or long-term oil/debris containment in and around marine facilities.

### **Features and Benefits:**

- ◆ **Heavy duty, high strength**, PVC-coated polyester conveyor belting membrane.
- ◆ Marine growth and UV inhibitors for years of **low maintenance**, 24 hour per day protection.
- ◆ **High visibility**, unsinkable rotary molded polyethylene floats filled with closed cell urethane foam.
- ◆ **ASTM** or **Universal** style marine grade aluminum boom connectors to mate with existing inventories.
- ◆ **Corrosion resistant** stainless steel hardware.

### **Canadyne Technologies Inc.**

12400 Vulcan Way  
Richmond, BC, V6V 1J8  
CANADA

Phone: 604.247.2297

Fax: 604.247.2298

Email: [info@canatec.com](mailto:info@canatec.com)

*"The right solution... the first time"*

# Canadyne PermaBoom Data Sheet



PermaBoom float (orange standard, yellow and black also available)

	PermaBoom 18	PermaBoom 24	PermaBoom 36
<b>Part Number</b>	10259	10266	10212
<b>Overall Height</b>	18 in (457 mm)	24 in (610 mm)	36 in (915 mm)
<b>Freeboard</b>	7 in (180 mm)	8 in (203 mm)	12 in (305 mm)
<b>Draft</b>	11 in (270 mm)	16 in (407 mm)	24 in (610 mm)
<b>Section Length</b>	50 feet (15.25m)	50 feet (15.25 m)	50 feet (15.25 m)
<b>Ballast</b>	Optional	Optional	Optional
<b>Tensile Strength</b>	27,000 lbs (12,270 kg)	36,000 lbs (16,350 kg)	54,000 lbs (24,500 kg)
<b>Boom Weight</b>	5.6 lbs/ft (8.3kg/m)	6.7 lbs/ft (10.0 kg/m)	7.5 lbs/ft (11.3 kg/m)



PermaBoom deployed around vessels in port (24 hour protection)

## Standard Features

- Boom fabric is heavy duty PVC-coated polyester conveyor belting, black
- Standard fabric weight 170 oz/yd<sup>2</sup> (5700 gsm), 0.20 inch (5mm) thick
- Standard fabric strength 1500 lbs/inch (267 kg/cm)
- Fabric has UV and marine growth inhibitors, chemical resistant
- Fully enclosed, rotary molded high density polyethylene float shells filled with closed cell polyurethane foam filling, impact resistant, unsinkable
- Floats are bolted through molded elliptical holes to allow stretching of boom skirt under tension
- Float weight 8 lbs (3.6 kg), 34.75 x 9.75 x 9.25 in (891 x 248 x 235 mm)
- 304 Stainless Steel (SS) float attachment and connector hardware
- Floats come disassembled from belting to minimize freight volume
- Full factory support for spares, repairs and technical assistance

## Optional Features

- Upgrade to heavier PVC fabric for increased abrasion resistance
- ASTM, Stainless Steel (SS) Hinge and Pin, or bolted connections
- Custom sizes, section lengths

## Recommended Accessories

- Towing Bridle and Tow Line
- Anchor Assembly systems
- Tidal compensators and dock seals



PermaBoom anchored in position with heavy duty mooring float

*"The right solution... the first time"*