

Canadyne PowerPack Model DH10Y-1E

Part No. 60037

SPECIFICATION	<u>IMPERIAL</u>	METRIC	
Prime Mover	Yanmar Diesel, air cooled		
Engine Power, nominal	10 HP	7.5 kW	
Drive	Hydraulic		
Length	39 inches	991 mm	
Width	35 inches	889 mm	
Height	36 inches	914 mm	
Approx. Weight, empty	250 pounds	113 kg	
Start	Recoil / Electric		
Engine Controls	Start / Stop, Speed		
Independent Hydraulic Circuits	1		
Hydraulic Controls	Speed, Direction (Single control)		
Gauges	Hydraulic Pressure, Oil Temperature, Level		
Hydraulic Pump	Direct Coupled Gear Pump		
Portability	Heavy duty tires, fold down handles		
Frame, Finish	Aluminum, powder coated orange		
Hydraulic Tank Capacity	6 US Gallons	20 L	
Hydraulic Hose, Fittings	2 x 15 m (50 ft) hydraulic hoses (1 pressure, 1 return) with		
,	brass quick connect fittings		

E-mail: info@canatec.com

Web: www.canatec.com

Phone: **+604.247.2297**

+604.247.2298



Canadyne PowerPack Model DH10Y-2E

Part No. 60039

SPECIFICATION	IMPERIAL	<u>Metric</u>
Prime Mover	Air-cooled diesel, Yanmar	
Power	10 HP	7.5 kW
Drive	Hydraulic	
Length	39 inches	991 mm
Width	35 inches	889 mm
Height	36 inches	914 mm
Approx. Weight, empty	260 pounds	120 kg
Start	Recoil / Electric	
Engine Controls	Start / Stop, Speed	
Independent Hydraulic Circuits	2 (one for transfer pump, one for skimmer head)	
Hydraulic Controls	Speed, Direction (Dual controls)	
Gauges	Hydraulic Pressure, Oil Temperature, Level	
Pump	Hydraulic, Direct Coupled Gear Pump	
Portability	Heavy duty tires, fold down handles	
Frame, Finish	Aluminum, powder coated orange	
Hydraulic Tank Capacity	6.1 US Gallons	23 litres
Hydraulic Hose, Fittings	4 x 15 m (50 ft) hydraulic hoses (2 x pressure, 2 x return) with brass quick connect fittings	

All above values are nominal and subject to change without notice.



E-mail: info@canatec.com

www.canatec.com

Phone: **+604.247.2297**

+604.247.2298



FEATURES AND ADVANTAGES OF CANADYNE POWERPACKS

- Aluminum construction, powder coat finish (others may offer unfinished aluminum, or painted steel frame which will be heavier, require frequent repainting and can corrode in marine environment.
- Wheeled cart with heavy duty tires and fold down handles (reduces storage)
- Recoil start AND electric start (others may offer recoil only)
- Brass quick connect fittings (others may use plated steel)
- Direction and speed controls, fully independent circuits
- High quality pressure compensated flow control valves
- Oil level and temperature gauges
- Large hydraulic tank (for hot climates) with filter.
- No rotating or exposed parts (direct coupled gear pump)



Phone: +604.247.2297

+604.247.2298

Fax: